

EKOKAT DEKO COAT - TRAVERTINE

Decorative Mineral Coat - Travertine



DESCRIPTION

The product is a cement-based, high strength, decorative mineral siding with special additives, silicon and micro fiber content, a travertine texture.

PROPERTIES

It has high water vapor permeability. It allows buildings to breathe. It is resistant to external influences thanks to its content of special additives. It has water impermeability. It has a natural and decorative appearance. It is easy to apply. It can be painted with exterior surface paints.

TECHNICAL SPECIFICATIONS

Appearance	Grey, White
Mixing Ratio	5.5-6 lt water /25 kg
Granule Size	> 3 mm
Amount of Consumption	12 - 13 kg/m ² (for a thickness of 1 cm)
Application Temperature	+5 °C to +35 °C
Capillary Water Absorption	0.3 kg/m ² .h ^{0.5} (W1)
Fire Reaction Class	A1
Pressure Strength	> 3.5 N/mm ² (CS III)
Dry Mortar Density	1550 ± 100 kg/m ²
Bending Strength	> 1 N/mm ²
Water Vapor Permeability	25 µ

* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.

AREAS OF USE

It is used as a final coat material on cement-based plasters, on exterior surfaces, and in exterior thermal insulation systems of all the buildings.

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com



EKOKAT DEKO COAT - TRAVERTINE

Decorative Mineral Coat - Travertine

BENEFITS

It is easy to prepare and apply. It is ready for use. It provides high adherence to concrete and plastered surfaces. It is resistant to water and frost. It is not affected by temperature differences.

INSTRUCTIONS FOR USE

Dust, swollen coats, dirt, oil, etc. present at application areas must be cleaned from the surface. The surface should be clean, smooth, and sound. Before the application, the surface must be moistened and saturated with water under very hot and windy weather conditions.

25 kg of EKOKAT DEKO COAT - TRAVERTINE should be mixed with 6-6.5 liters of clean water on average with the help of a low revolving mixer until a homogeneous consistency is achieved. The mortar should be allowed to rest for 5 minutes before proceeding with the application and then mixed again. EKOKAT DEKO COAT - TRAVERTINE should be spread on the surface with equal thickness with a stainless steel trowel, and the application thickness must be adjusted to the largest pattern stone. Patterns should be given to the surface by a plastic trowel with circular motions. Patterns should be applied always when the mortar is wet. It may not be left on the face as a final coat material. Paint must be applied on top of it after drying. The recommended water ratio and rest times should be observed while preparing the mortar. Avoid from applying it under direct sunlight. Pre-prepared but hardened materials should not be included in newly prepared mortar. Do not apply above 35 ° C or below + 5 ° C. It should not be applied under very humid and / or hot weather conditions, or onto such surfaces that are being melted or are subject to the danger of frost within 24 hours.

NOTE: Foreign materials such as lime, cement, plaster, and sand should not be added to the prepared plaster.

PACKAGING

25 kg PE reinforced craft bags
64 shrink bags on one palette (110x110 cm).

STORAGE CONDITIONS AND SHELF LIFE



No more than two palettes should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions.

SAFETY MEASURES

Work clothes, protective gloves, goggles and masks suitable for workers health and safety should be used during the application. Due to irritant effects of uncured material, contact areas should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

■ EK 8005.020.25  White
■ EK 8005.001.25  Colored

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com

