

## EKOKAT PRIMER AAA - G

Plaster Primer Enhancing Adherence



### DESCRIPTION

It is an acrylic emulsion-based, dull, transparent plaster primer which is used to enhance adherence, and can be applied on all water-based plaster surfaces.

### FEATURES

It increases the adherence of the application plaster by reducing the absorbency of the surface. It ensures that materials to be applied are fully attached to surfaces. It is solvent free.

### TECHNICAL SPECIFICATIONS

Structure	Acrylic emulsion-based
Color	Transparent
Thinner	Water
Amount of Consumption	0.100 liters /m <sup>2</sup> depending upon surface roughness and absorbency
Drying Time	For application of the final coat of paint and coating material: 6 hours
Application Temperature	+5 °C to +35 °C
Application Tools	Roll, brush, spray gun

\* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.

### AREAS OF USE

It is applied on suitably prepared plaster surfaces on the inner surfaces of all buildings.

### BENEFITS

It is easy to prepare and apply. It is ready for use. It offers high adherence for plaster-applied surfaces. It is resistant to water and frost. It is not impacted from thermal differences

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com



## EKOKAT PRIMER AAA - G

### Plaster Primer Enhancing Adherence

#### INSTRUCTIONS FOR USE

Dust, swollen coats, dirt, oil, etc. present on application surfaces must be cleaned from the surface. Plaster-applied surfaces must be cleaned thoroughly.

If application is to be made on a new plaster-applied surface, then the surface is required to get dry. EKOKAT PRIMER ADD - G should be mixed thoroughly before application. EKOKAT PRIMER ADD - G should be diluted with water at the ratio of 1/7 by volume and mixed well until it becomes homogenous. It should be applied as a single coat by means of a brush, a roll, or a spraying system. A rest time of at least 6 hours should be allowed between coats for application of the final coat of paint and coating material. The ambient temperature and the temperature of the application surface should be at least +5°C during the application as well as for at least 24 hours thereafter. Application tools should be washed with water immediately after use.

#### PACKAGING

1 kg plastic buckets.

5 kg plastic buckets.

#### STORAGE CONDITIONS AND SHELF LIFE

No more than three buckets should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions.


#### SAFETY MEASURES

Work clothes, protective gloves, goggles and masks suitable for workers health and safety should be used during the application. Due to irritant effects of uncured material, it should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

#### RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

■ ■ ■ EK 1230.000.20

 Transparent

Date : 02.03.2017 Revision : 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com

