

EKOKAT FLOOR - WP

Waterproof Terrace Screed

DESCRIPTION

The product is a perlite-based lightweight alum that provides water and heat isolation by contributing to water isolation with its water repellent feature at terraces, balconies, and other wet areas, and that can be applied manually or with the help of a machine.

TECHNICAL SPECIFICATIONS

Color	Grey
Dry Unit Bulk Weight	500 ± 70 kg/m ³
Pressure Strength	C5 (TS EN 13813)
Bending Strength	F2 (TS EN 13813)
Fire Reaction Class	A1
Mixing Process	5 minutes of mixing-2 minutes of resting-2 minutes of mixing
Time for Use	2 hours
Time for Processing	20 minutes
Drying Time	4-6 days
Application Thickness	30 mm - 70 mm
Time Required Before Allowing Pedestrian Traffic	min. 2 days (This period might extend depending upon weather conditions)

* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.

AREAS OF USE

The product is used to provide water and heat isolation by contributing to water isolation at terraces, balconies, and other wet spaces.

Date : 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com



EKOKAT FLOOR - WP

Waterproof Terrace Screed

BENEFITS

- It is water repellent. Contributes to water insulation.
- High sound and thermal insulation
- Lightweight
- Practical and fast application
- Suitable for manual and machine applications
- Fireproof (A1 class)

APPLICATION CONDITIONS

- Ambient temperature of +5 ° C to +35 ° C.
- Avoid from application under very humid and / or very hot weather conditions.
- Avoid from applying it under direct sunlight and strong wind.
- It should not be applied on frozen, melted surfaces, or surfaces with frost hazard within 24 hours.

INSTRUCTIONS FOR USE

The application surface must be clean, be free of powder and grease, be solid and dry. 15-17 liters of water on average should be added to a 35 kg bag of EKOKAT Insulated Terrace Screed, and mixed in the application machine, and the prepared mortar should be applied by spraying. In manual applications, the mixture must be prepared with a low revolving mixer in accordance with the specified mixing times, and applied to the surface with a steel trowel. Depending on climatic conditions, starting one day after application, the surface will be watered in the shade twice in the morning and evening for at least 3 days.

WARNING: EKOKAT Insulated Terrace Screed is not a waterproofing material in itself. The application of EKOKAT DRYSEAL FLEX two-component waterproofing material before or after the application of EKOKAT Insulated Terrace Screed would give an exact solution for achieving water insulation. No foreign materials should be added into the mortar. Each bag should be used as a whole and attention should be paid to the water rates specified. All tools used should be washed with water after application before drying. The stated times are valid at a surface and ambient temperature of 20 ° C. The time is shortened at high temperatures and extended at low temperatures.

PACKAGING

35 kg craft bags on shrink palettes.

CONSUMPTION

8 kg/m² for a screed thickness of 1 cm.

APPLICATION TOOLS

Screed application machine, low revolving mixer, jig, steel trowel.

APPLICATION SURFACE

Gross Concrete, Concrete, and Cement-based Leveling Concrete

STORAGE CONDITIONS AND SHELF LIFE

It should be stored in its unopened original packaging, in a cool and dry environment. Avoid from exposure to direct sunlight. Shelf life is one year from date of production under suitable storage conditions.

Date : 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com



EKOKAT FLOOR - WP

Waterproof Terrace Screed

APPLICATION RESTRICTIONS

It should not be applied directly on metal, wooden, or wooden-top surfaces. Do not apply it on plaster surfaces.

SAFETY MEASURES

Work clothes, protective gloves, goggles and masks suitable for workers health and safety should be used during the application. Due to irritant effects of uncured material, it should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

S22: Do not breathe dust.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S29: Do not empty into drains.

S24/25: Avoid eye and skin contact.

S37/39: Wear suitable protective clothing, gloves and eye/face protection.

S46: If swallowed, seek medical advice immediately and show this container or label

Risk Phrases

R7/8: Irritates the respiratory tract and skin.

R41: Risk of serious damage to eyes.

R43: May cause sensitisation by skin contact.

RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

■ ■ ■ ■ ■ EK 9004.010.25

 Grey

Date : 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir
TURKEY
T. +90 216 457 80 10 F. +90 216 457 82 60
info@ekokat.com www.ekokat.com

