

## EKOKAT PRIMER EXTO - S

### Exterior Wall Primer with Silicon



#### DESCRIPTION

The product is an acrylic emulsion-based, matt, pigmented primer with silicon additives that can be applied under all water-based interior paint and coating materials.

#### PROPERTIES

It reduces the consumption of paint and coating material, on which the application is to be made, by reducing the absorbency of the surface. It ensures that materials to be applied are fully attached to surfaces. It is solvent free. It is thinned with water. It is a water-based product so it does not harm the environment and human health.

#### TECHNICAL SPECIFICATIONS

Structure	Acrylic emulsion-based
Color	White & colors available in EKOKAT COLOR paint colors chart
Thinner	Water
Amount of Consumption	0.100 lt /m <sup>2</sup> depending upon surface roughness and absorbency
Drying Time	For application of the final coat of paint and coating material: 6 hours
Application Temperature	+5 °C to +35 °C
* The above values are valid for + 23°C and 50% relative humidity. The time is shortened at high temperatures and extended at low temperatures.	

#### AREAS OF USE

It is applied on appropriately prepared mineral surfaces such as black plaster, concrete, or cement board at interior and exterior spaces of all buildings, and is also applied on old painted surfaces.

#### BENEFITS

It is easy to prepare and apply. It is ready for use. It provides high adherence to concrete and plaster-applied surfaces. It is resistant to water and frost. It is not affected from temperature differences.

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DIŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com



## EKOKAT PRIMER EXTO - S

### Exterior Wall Primer with Silicon

#### INSTRUCTIONS FOR USE

Dust, swollen coats, dirt, oil, etc. present on application surfaces must be cleaned from the surface. Surfaces with old paints and synthetic surfaces should be cleaned thoroughly. If application is to be made on new mineral surfaces, the surface should be cured for at least 28 days. Surfaces should be repaired using EKOKAT PASTE INTO – TCK, if necessary. EKOKAT PRIMER EXTO – S should be mixed thoroughly before application. EKOKAT PRIMER EXTO – S should be diluted with 20% by volume of water and mixed well until it becomes homogenous. It should be applied as a single coat by means of a brush, a roll, or a spraying system. A rest time of at least 6 hours should be allowed to lapse between coats for the application of the final coat of paint and coating material. The ambient temperature and the temperature of the application surface should be at least +5°C during the application as well as for at least 24 hours thereafter. Application tools should be washed with water immediately after use.

#### APPLICATION TOOLS

Roll, brush, spray gun

#### PACKAGING

20 kg plastic buckets

#### STORAGE CONDITIONS AND SHELF LIFE

No more than three buckets should be placed on top of each other in their unopened original packaging, in a cool and dry environment. Shelf life is 12 months from date of production under suitable storage conditions.

#### SAFETY MEASURES

Work clothes, protective gloves, goggles, and masks suitable for workers health and safety should be used during the application. It should be washed with plenty of water and soap immediately in case of contact with skin and eyes. If swallowed, seek medical advice immediately. No food and drink should be brought into application areas. Store it out of reach of children. Please refer to the safety data sheet for further information.

#### RESPONSIBILITY

Our Company may not be held liable for any application errors that might be suffered if the product is not used for its intended purposes, or if it is failed to conform to the conditions and proposals specified above regarding technical application. This technical data sheet contains information that is current as of the date of issuance hereof. The manufacturer hereby reserves its right to change this data sheet at any time.

EC 422K.001.20

White

Date: 02.03.2017 Revision: 00

ÇULLAS YAPI MALZEMELERİ SANAYİ ve DİŞ TİCARET A.Ş.  
Çoraklar Mahallesi 5024 Sokak No:10 Aliğa Organize Sanayi Bölgesi - Aliğa / İzmir  
TURKEY  
T. +90 216 457 80 10 F. +90 216 457 82 60  
info@ekokat.com www.ekokat.com

